







PRODUCT FEATURES

Z-Wave

- 10 scene triggers per rocker
- Fits System 55 frames
- Firmware update (OTA)
- SmartStart
- Wireless battery-operated wall switch
- Designed for controlling lights, blinds, relays, dimmers etc.
- Controls up to 3 seperate groups and 5 devices per group
- Easy to install with screws or double-sided adhesive tape
- Supports encryption modes S0, S2 Authenticated Class, S2 Unauthenticated Class

PRODUCT DATA	
Ambient temperature range in use	5 to 40°C
Ambient temperature range in storage	0 to 40°C
Min. and max ambient humidity (RH%)	10 to 85%
Colour	White RAL 9010

ADDITIONAL INFO	
IP Code	IP20
Certification	Reach, RoHS
Warranty international	2 years
Customs number	85437000

HEATIT Z-PUSH WALL CONTROLLER WHITE RAL 9010 GLOSSY

Battery operated wall switch

Art.no 4512646

GTIN 7071236017417

The Heatit Z-Push Wall Controller is a wireless wall-mounted Z-Wave Controller. It has mounting options for 1, 2 or 3 rockers, allowing for easy and practical management of your Z-Wave products. The switch can be set up to control scenarios or work in association with other Z-Wave products. Each rocker switch has a dual-color LED to indicate button actions.

The Wall Controller is coin cell battery powered.

The product is intended primarily for residential applications.

Supplied in glossy white and black matt finish.

IOT / SMART HOME SPECIFIC DATA		
Z-Wave Frequency	Z-Wave - 868.4 MHz (EU)	
Z-Wave Chip	Z-Wave 700 chip	
Z-Wave encryption mode	S0 S2 Unauthenticated Class S2 Authenticated Class	
Min radio frequency range	40m	
Push buttons	1, 2 or 3	
Over The Air update (OTA)	Yes	

ELECTRO TECHNICAL DATA		
Voltage	Battery	
Battery type	CR2450 3V	
Number of batteries required	1	
Battery current	3V	













PRODUCT DIMENSIONS				
50mm	Product Width	100mm		
110mm	Product net weight	73g		

MAINTENANCE

The device is maintenance-free. Indoor use only.

ADDITIONAL INFORMATION

The product must be used with a security-enabled Z-Wave Controller in order to fully utilize security/encryption.

Supplied with 1, 2 or 3 rockers.

Standards: 1999/5/EC (RTTE), 2002/96/EC (WEEE), CE, RoHS 2002/95/EC, Z-Wave Plus

RETURN AND RECYCLING

The product must be recycled as electronic waste.

DISCLAIMER

Warranty does not apply to batteries.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.











Heatit Z-Push Wall Controller White RAL 9010 GLOSSY can be ordered from 画無回www.heatit.com/4512646

All additional documentation are available on the above adress and on documents.heatit.com/4512646







