











# **PRODUCT FEATURES**

Z-Wave

Wireless battery-operated wall switch

Designed for controlling lights, blinds, relays, dimmers etc.

Fits System 55 frames

SmartStart

Controls up to 3 seperate groups and 5 devices per group 10 scene triggers per rocker

Easy to install with screws or double-sided adhesive tape Firmware update (OTA)

Supports encryption modes S0, S2 Authenticated Class, S2 Unauthenticated Class

# HEATIT Z-PUSH WALL CONTROLLER BLACK MATT

Battery operated wall switch

**Art.no** 4512694

**GTIN** 7071236015741

The Heatit Z-Push Wall Controller is a wireless wall-mounted Z-Wave Controller. It has mounting options for 1, 2 or 3 rockers, allowing for easy and practical management of your Z-Wave products. The switch can be set up to control scenarios or work in association with other Z-Wave products. Each rocker switch has a dual-color LED to indicate button actions.

The Wall Controller is coin cell battery powered. The product is intended primarily for residential applications.

Supplied in glossy white and black matt finish.

IOT / SMART HOME SPECIFIC DATA		
Z-Wave Frequency	Z-Wave - 868.4 MHz (EU)	
Z-Wave Chip	Z-Wave 700 chip	
Min radio frequency range	40m	
Over The Air update (OTA)	Yes	
Push buttons	1	
	2 push buttons	
	3	
Z-Wave encryption mode	SO	
	S2 Unauthenticated Class	
	S2 Authenticated Class	

ELECTRO TECHNICAL DATA	
Voltage	Battery
Battery type	CR2450 3V
Number of batteries required	1
Battery current	3V









## **MAINTENANCE**

The device is maintenance-free. Indoor use only.

# **ADDITIONAL INFORMATION**

The product must be used with a security-enabled Z-Wave Controller in order to fully utilize security/encryption.

Supplied with 1, 2 or 3 rockers.

# PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

ST	Λ	NI.	$\mathbf{n}$	А	Ю	п	
<b>7</b> I	н	w	.,	м	к		-

Certification	RoHS	EN Standards	Z-Wave Plus
Reach		RoHS 2002/95/EC	
			CE
			1999/5/EC (RTTE)
			2002/96/EC (WEEE)
IP Code	IP20		2002/ 30/ E

#### **WARRANTY**

Warranty Norway 5 years Warranty international 2 years

# **LOGISTICAL DATA (F-PACK)**

Width	57mm	Height/diameter	88mm
Length	86mm	Weight	128g
GTIN	7071236015741	Unit	BOX
Consists of unit	EA	Quantity	1

# **LOGISTICAL DATA (M-PACK)**

Width	270mm	Height/diameter	130mm
Length	360mm	Weight	3300g
GTIN	-	Unit	CARTON
Consists of unit	ВОХ	Quantity	24











LOGISTICAL DATA (D-PACK)				
Width	380mm	Height/diameter	298mm	
Length	565mm	Weight	13800g	
GTIN	-	Unit	CARTON	
Consists of unit	CARTON	Quantity	96	

### **DISCLAIMER**

Warranty does not apply to batteries.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com
Heatit Controls AB can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.







# Heatit Z-Push Wall Controller Black Matt can be ordered from www.heatit.com/4512694



All additional documentation are available on the above adress and on documents.heatit.com/4512694



