



PRODUCT FEATURES

Z-Wave
 Wireless battery-operated wall switch
 Designed for controlling lights, blinds, relays, dimmers etc.
 Fits System 55 frames
 SmartStart
 Controls up to 3 separate groups and 5 devices per group
 10 scene triggers per rocker
 Easy to install with screws or double-sided adhesive tape
 Firmware update (OTA)
 Supports encryption modes S0, S2 Authenticated Class, S2 Unauthenticated Class

HEATIT Z-PUSH WALL CONTROLLER BLACK MATT

Battery operated wall switch

Art.no 4512694

GTIN 7071236015741

The Heatit Z-Push Wall Controller is a wireless wall-mounted Z-Wave Controller. It has mounting options for 1, 2 or 3 rockers, allowing for easy and practical management of your Z-Wave products. The switch can be set up to control scenarios or work in association with other Z-Wave products. Each rocker switch has a dual-color LED to indicate button actions.

The Wall Controller is coin cell battery powered. The product is intended primarily for residential applications.

Supplied in glossy white and black matt finish.

IOT / SMART HOME SPECIFIC DATA

Z-Wave Frequency	Z-Wave - 868.4 MHz (EU)
Z-Wave Chip	Z-Wave 700 chip
Min radio frequency range	40m
Over The Air update (OTA)	Yes
Push buttons	1 2 push buttons 3
Z-Wave encryption mode	S2 Authenticated Class S0 S2 Unauthenticated Class

ELECTRO TECHNICAL DATA

Voltage	Battery
Battery type	CR2450 3V
Number of batteries required	1
Battery current	3V



MAINTENANCE

The device is maintenance-free. Indoor use only.

ADDITIONAL INFORMATION

The product must be used with a security-enabled Z-Wave Controller in order to fully utilize security/encryption.

Supplied with 1, 2 or 3 rockers.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

STANDARDS

EN Standards	CE Z-Wave Plus RoHS 2002/95/EC 1999/5/EC (RTTE) 2002/96/EC (WEEE)	Certification	Reach RoHS
IP Class	IP20		

WARRANTY

Warranty Norway	5 years	Warranty international	2 years
-----------------	---------	------------------------	---------

LOGISTICAL DATA (F-PACK)

Width	57mm	Height/diameter	88mm
Length	86mm	Weight	128g
GTIN	7071236015741	Unit	BOX
Consists of unit	EA	Quantity	1

LOGISTICAL DATA (M-PACK)

Width	270mm	Height/diameter	130mm
Length	360mm	Weight	3300g
GTIN	-	Unit	CARTON
Consists of unit	BOX	Quantity	24

**LOGISTICAL DATA (D-PACK)**

Width	380mm	Height/diameter	298mm
Length	565mm	Weight	13800g
GTIN	-	Unit	CARTON
Consists of unit	CARTON	Quantity	96

DISCLAIMER

Warranty does not apply to batteries.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com

Heatit Controls AB can not be held liable for any type of errors or omissions in our product information.

Product specifications may change without further notice.



Heatit Z-Push Wall Controller Black Matt can be ordered from www.heatit.com/4512694

All additional documentation are available on the above adress and on documents.heatit.com/4512694

